

BLEEM





## BLEEM

BLEEM stands for compact and modern design that fits into every shop design. With its slim proportions the LED luminaire sets modern accents. At the same time the customer's customised colour scheme can be incorporated into the luminaire design by the lateral lug being available in any colour required.



### SPECIAL LENS

The light transmission is three-dimensional and uniform, and the light shadow contour is more beautiful.



### POWER PACKAGE

- White light colours up to 4000 lm
- Special light spectrums for the fresh-food area up to 4000 lm



### EFFICIENT LIGHTING

6 % more light and 34 % more efficiency (in comparison to HIT 70 W)






### ELEGANT DESIGN


Classic design with elegant proportions – Bleem fits into every shop design




### WELL PROTECTED

Optional glass cover to protect from dirt




Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700 K, 3000 K, 3000 K - Efficient White, 3000 K - Brilliant Colour, 3500 K, 4000 K
Light colour Food*	M, M+F, BF
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9006 white aluminium RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Lighting controls	On request
Weight	0.68kg
Test seal	




### Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	FUNTION
GMT121	20W	120LM/W	Ø68*H130mm	15°/24°/38°	90	ON/OFF DIM/DALI


15°-3000K-CRI90



24°-3000K-CRI90



38°-3000K-CRI90




### Accessories




SOLITE  
SOFTENING  
LENS



HONEY  
COMB


Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700 K, 3000 K, 3000 K - Efficient White, 3000 K - Brilliant Colour, 3500 K, 4000 K
Light colour Food*	M, M+F, BF
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9006 white aluminium RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Lighting controls	On request
Weight	0.74kg
Test seal	




### Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	FUNTION
GMT121	30W	120LM/W	Ø68*H155mm	15°/24°/38°	90	ON/OFF DIM/DALI


15°-3000K-CRI90



24°-3000K-CRI90



38°-3000K-CRI90




### Accessories




SOLITE  
SOFTENING  
LENS



HONEY  
COMB


Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700 K, 3000 K, 3000 K - Efficient White, 3000 K - Brilliant Colour, 3500 K, 4000 K
Light colour Food*	M, M+F, BF
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9006 white aluminium RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Lighting controls	On request
Weight	0.82kg
Test seal	




### Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	FUNTION
GMT121	30W	120LM/W	Ø81*H146mm	15°/24°/38°	90	ON/OFF DIM/DALI


15°-3000K-CRI90



24°-3000K-CRI90



38°-3000K-CRI90




### Accessories




SOLITE  
SOFTENING  
LENS



HONEY  
COMB


Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700 K, 3000 K, 3000 K - Efficient White, 3000 K - Brilliant Colour, 3500 K, 4000 K
Light colour Food*	M, M+F, BF
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9006 white aluminium RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Lighting controls	On request
Weight	0.96kg
Test seal	




### Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	FUNTION
GMT121	40W	120LM/W	Ø81*H160mm	15°/24°/38°	90	ON/OFF DIM/DALI


15°-3000K-CRI90



24°-3000K-CRI90



38°-3000K-CRI90



### Accessories



SOLITE  
SOFTENING  
LENS



HONEY  
COMB