

DOTAGE





DOTAGE

DOTAGE as linear lighting which have widely beam angle 120D , apply as general light . Have three different choice on the size and power.



SLIM SIZE
The track system is more slim in low voltage




EASY INSTALLATION





RA
High CRI up to 97



RELIABLE
Branded component ensure the lighting have reliable quality




Product series	DOTAGE
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Separated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	DC48V
Lighting controls	On Request
Weight	0.25kg
Test seal	









Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	FUNTION
GMT301	10W	120LM/W	L220*22	110°	48V	90	ON/OFF DIM/DALI

110°-3000K-CRI90




Product series	DOTAGE
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Separated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	DC48V
Lighting controls	On Request
Weight	0.487kg
Test seal	    





Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	FUNTION
GMT301	12W	120LM/W	L328*22	110°	48V	90	ON/OFF DIM/DALI

110°-3000K-CRI90




Product series	DOTAGE
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Separated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	DC48V
Lighting controls	On Request
Weight	0.56kg
Test seal	




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	FUNTION
GMT301	20W	120LM/W	L545*22	110°	48V	90	ON/OFF DIM/DALI

110°-3000K-CRI90



Product series	DOTAGE
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Separated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	DC48V
Lighting controls	On Request
Weight	0.712kg
Test seal	



Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	FUNTION
GMT301	40W	120LM/W	L1196*W32*H52	110°	48V	90	ON/OFF DIM/DALI

110°-3000K-CRI90

