



MAGEN

MAGEN is the simplest of cylinders. The exterior is clean with no visible seams or hardware. Inside, a wealth of technology remains hidden.



STRUCTURE

Machined aluminum tube offered with textured black, white finish. MAGEN can be specified with 2 baffle finishes: white or black.



OPTIC

Designed with narrow or medium beam angle, to meet all applications. Optical choice of clear, frosted or honeycomb lenses available.





Reliable

Reliable
Branded component ensure the lighting have reliable quality.











Product series MAGEN

Application areas Accent lighting

Mounting Power Track

Lighting technology LED

LED Luminous Flux Class 120LM/W

Light colour White 2700 K, 3000 K,

3500 K, 4000 K, 5000K

Cooling Passive

Supply unit Driver Separated

Luminaire colour RAL 9005 jet black

RAL 9016 traffic white

Special colours on request


Surface Structure powder-coated

Nominal voltage DC48V

Lighting controls On Request

Weight





Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	FUNTION	
GMT601	6W	120LM/W	Ф30*420	15°/24°/36°	48V	90	ON/OFF DIM/DALI	
15°-3000K-CRI90			24°-3000K-CRI9	0	36°-3000	K-CRI90		
60° 180 60° 45° 45°	100 412 450 450 4103 4103 4103 4103 4103 4103 4103 410	0.30 0.61 0.91	90° 180° 180° 180° 180° 180° 180° 180° 18	60 2m 2112 1. 3m 1144 1. 30 4m 53 2.	30° 30° 30° 30° 30° 30° 30° 30° 30° 30°	180°	60° 1m 446 50° 2m 111 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	D/B(m) 0.69 1.38 2.07