

MAGA





MAGA

MAGA made of die-cast aluminium and thermoplastic material. Opti Beam inter-changing reflectors with high luminous efficiency and uniform distribution.



FLEXIBLE INTSALLTION

Inclination of 90° on horizontal plane and 360° rotation around the vertical axis, with mechanical aiming lock.



HIGH CRI

LED versions with high color rendering index. High visual comfort



RELIABLE

Branded component ensure the lighting have reliable quality.



FOOD




FASHION




SHOP



AUTOMOBILE


Product series	MAGA
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Separated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	DC48V
Lighting controls	On Request
Weight	0.436kg
Test seal	



Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	FUNTION
GMT401	3W	120LM/W	Φ30*60	15°/24°/36°	48V	90	ON/OFF DIM/DALI

15°-3000K-CRI90




Accessories




SOLITE
SOFTENING
LENS



HONEY
COMB


Product series	MAGA
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Separated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	DC48V
Lighting controls	On Request
Weight	0.436kg
Test seal	




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	FUNTION
GMT401	6W	120LM/W	Φ35*68	15°/24°/36°	48V	90	ON/OFF DIM/DALI


15°-3000K-CRI90



24°-3000K-CRI90



38°-3000K-CRI90




Accessories




SOLITE
SOFTENING
LENS



HONEY
COMB


Product series	MAGA
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Separated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	DC48V
Lighting controls	On Request
Weight	0.62kg
Test seal	



Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	FUNTION
GMT401	8W	120LM/W	Φ44*82	15°/24°/36°	48V	90	ON/OFF DIM/DALI


15°-3000K-CRI90




Accessories




SOLITE
SOFTENING
LENS



HONEY
COMB


Product series	MAGA
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Separated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	DC48V
Lighting controls	On Request
Weight	0.66kg
Test seal	




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	FUNTION
GMT401	15W	120LM/W	Ø55*138	15°/24°/36°	48V	90	ON/OFF DIM/DALI


15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90



Accessories



SOLITE
SOFTENING
LENS



HONEY
COMB