



MAX

The design of the MAX series is more slender and compact, with a simple appearance and structure, using high-grade matte black equipped with high-grade chips, and continuous luminescence, bringing you a new scene lighting experience.



SIMPLE DESIGN

Tilt range, 350° in horizontal. 2. optical lens: the light is pure and not dazzling, different color temperature to meet different needs



METHODS TO INSTALLATION

Catering to personalized installation needs




APPLY TO

Gallery, jewelry store, exhibition, showroom, fashion shop




FOOD




FASHION




SHOP



AUTOMOBILE


Product series	MAX
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Lighting controls	On request
Weight	0.23kg
Test seal	




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	FUNTION
GMT221	7W	90-100LM/W	35*H80mm	15°/24°/36°	90	ON/OFF DIM/DALI


15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90




Accessories




SOLITE
SOFTENING
LENS



HONEY
COMB


Product series	MAX
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Lighting controls	On request
Weight	0.23kg
Test seal	




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	FUNTION
GMT221	12W	90-100LM/W	45*H100mm	15°/24°/36°	90	ON/OFF DIM/DALI


15°-3000K-CRI90



24°-3000K-CRI90



36°-3000K-CRI90




Accessories




SOLITE
SOFTENING
LENS



HONEY
COMB


Product series	MAX
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Lighting controls	On request
Weight	0.23kg
Test seal	




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	FUNTION
GMT221	17W	90-100LM/W	55*H120mm	15°/24°/36°	90	ON/OFF


15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90




Accessories




SOLITE
SOFTENING
LENS



HONEY
COMB


Product series	MAX
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Lighting controls	On request
Weight	0.23kg
Test seal	




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	FUNTION
GMT221	23W	90-100LM/W	65*H140mm	15°/24°/36°	90	ON/OFF


15°-3000K-CRI90



24°-3000K-CRI90



36°-3000K-CRI90



Accessories



SOLITE
SOFTENING
LENS



HONEY
COMB