



FON

FON series, with a fixed Angle of 180°, the light is uniform and easy to adjust their radiation, accurate lighting, high color display index up to 97 to show the true color of the exhibits.



SLIDABLE DESIGN

Tilt range, 350° in horizontal. 2. optical lens: the light is pure and not dazzling, different color temperature to meet different needs.




METHODS TO INSTALLATION

Catering to personalized installation needs.




APPLY TO

Gallery, Jewelry Store, Exhibition, Showroom, Fashion Shop




Product series	FON
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V,50/60Hz
Lighting controls	On request
Weight	Approx. 0.31KG
Test seal	<div> <div>ERC</div> <div>CE</div> <div>IP20</div> <div> </div> <div> </div> <div> </div> <div> </div> </div>




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT213	30W	90-100LM/W	91*H112mm	36°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

MAX ANGLE




MAX ANGLE



Accessories



SOLITE
SOFTENING
LENS



HONEY
COMB